

Datum: 22.07.2024



(slika je simbolična)

Ploska sesalna šalčka, okrogla, material NBR, »PFG« Ø: 25 mm

Kategorija: [Flat suction pad, round, material NBR](#)
Šifra: **108439RIE**

Kratek opis

Flat suction cup, round, Material NBR, »PFG«, ø:25 suitable connection nipple IT G 1/8, suitable connection nipple ET G 1/8

Robust and hard-wearing suction pad with a single sealing lip.

Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to handle smooth or slightly rough surfaces. Due to its flat shape, it can grip the workpiece in a very short time and withstand the forces that result from fast movement of the object during handling. It acts as the connecting element between the vacuum generator and the workpiece.

Properties:

- Very short evacuation times
- Suitable for high lateral forces
- Good intrinsic stability when attached to the load
- Supports on the bottom
- Very short cycle times
- High suction forces with small dimensions

Applications:

Handling workpieces with smooth or slightly rough surfaces, e.g. metal sheets, cardboard boxes, sheets of glass, plastic parts and sheets of wood.

Tehnične Specifikacije

Primerna povezava priključka z notranjim navojem	G 1/8
Primerna povezava priključka z zunanjim navojem	G 1/8
Prostornina [cm ³]	1.300
Ø notranje cevi [mm]	4
Višina priključka z notranjim navojem [mm]	19.0
Min. izbočen polmer krivine [mm]	25
Premer [mm]	25
Sesalna sila [N]	26.5
Višina priključka z zunanjim navojem [mm]	30.0