



(slika je simbolična)

Polnilna enota »FUTURA-mali«, Elektr. vodena, 24 V DC, G 1/4

Kategorija: [Filling unit, electrically operated, 24 V DC](#)
Šifra: **142526RIE**

Kratek opis

Filling unit »FUTURA-mini«, electr. actuated with solenoid 24 V DC, 2.5 watt, Size 0, G 1/4, Exhaust G 1/4, Input pr. 2.5 - 10 bar

The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.

The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).

It is connected and disconnected by means of the 3/2-way valve.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Električni priključek	Socket coupling EN 175301-803, form C, poles 2+PE
IP zaščita	IP 65
Izpušni zrak	G 1/4 At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Merjenje pretoka	G 1/4
Navoj	PA66 GF60
Ohišje	Plastic
Priključni navoj	FUTURA-mini
Serija	Compressed air, neutral gases
Srednje	
Zaklepna moč pri 50 Hz AC napetosti [VA]	1.6
Dvižna moč pri 50 Hz AC napetosti [VA]	2.2
Min. vhodni tlak [bar]	2.5
Vhodna moč	2.5 Watt with DC voltage
Max. vhodni tlak [bar]	10
Max. temperaturno območje [°C]	50
A [mm]	86.0
C [mm]	93.0
Delovni cikel [%]	100
B [mm]	138.0
Pretok [l/min]	1400