

Datum: 03.07.2024



(slika je simbolična)

## Polnilna enota »FUTURA-mali«pnevm. vodenaVel. 0G 1/4

Kategorija: [Filling unit, pneumatically operated](#)  
Šifra: **142529RIE**

### Kratek opis

Filling unit »FUTURA-mini«, pneumatically actuated, Size 0, G 1/4, Exhaust G 1/4, Input pressure 2.5 - 12 bar, Temp. -10°C to 50°C  
The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.  
The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).  
It is connected and disconnected by means of the 3/2-way valve.  
The filling time can be altered by turning the adjusting screw.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Merjenje pretoka	At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Navoj	G 1/4
Ohišje	PA66 GF60
Priključni navoj	Plastic
Serija	FUTURA-mini
Srednje	Compressed air, neutral gases
Min. vhodni tlak [bar]	2.5
Max. vhodni tlak [bar]	12
Max. temperaturno območje [°C]	50
C [mm]	60.0
A [mm]	86.0
B [mm]	105.0
Pretok [l/min]	1400