

Datum: 24.08.2024



## Polnilna enota »FUTURA«, pnevmatsko vodena, Velikost 4, G 1

Kategorija: [Filling units, pneumatically operated](#)  
Šifra: **156637RIE**

(slika je simbolična)

### Kratek opis

Filling unit »FUTURA«, pneumatically actuated, Size 4, G 1, Exhaust G 1/2, Input pressure 2.5 - 16 bar, Temp. -10 °C to 50 °C

The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.

The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).

It is connected and disconnected by means of the 3/2-way valve.

The filling time can be altered by turning the adjusting screw.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/2 At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Merjenje pretoka	G 1
Navoj	PA66 GF60
Ohišje	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	
Min. vhodni tlak [bar]	2.5
Velikost	4
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
D [mm]	67.0
C [mm]	78.0
B [mm]	145.0
A [mm]	170.0
Pretok [l/min]	9000