

Datum: 02.10.2024



(slika je simbolična)

## Poseben filter »Stinard« Kov. pos.0.01 µmVel. 3G 1/2

Kategorija: [Special filter with metal bowl](#)Šifra: **101003RIE**

### Kratek opis

Special filter »Standard« with metal container, 0.01 µm, Size 3, G 1/2, Input pressure max. 25 bar, Med. / ambient temp. max. 50°C

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

### Tehnične Specifikacije

Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serija	Standard
Rang filtra [µm]	0.01
Velikost	3
DN	15
C [mm]	18.0
Max. vhodni tlak [bar]	25
H [mm]	50.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	79.0
Učinkovitost [%]	99.999
D [mm]	171.0
Pretok [l/min]	1250