

Datum: 30.12.2024



(slika je simbolična)

Poseben filter »Stinard« Kov. pos.0.01 µmVel.1,G 1/4

Kategorija: [Special filter with metal bowl](#)
Šifra: **101000RIE**

Kratek opis

Special filter »Standard« with metal container, 0.01 µm, Size 1, G 1/4, Input pressure max. 25 bar, Med. / ambient temp. max. 50°C

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At P ₂ = 6 bar and pressure drop Δ _p = 1 bar |
| Navoj | G 1/4 |
| Odtok kondenzata | Manuel |
| Ohišje | Die-cast zinc, painted silver |
| Posoda | Metal container |
| Serija | Standard |
| Rang filtra [µm] | 0.01 |
| Velikost | 1 |
| DN | 6 |
| C [mm] | 14.0 |
| Max. vhodni tlak [bar] | 25 |
| H [mm] | 38.0 |
| A [mm] | 48.0 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| Učinkovitost [%] | 99.999 |
| D [mm] | 133.5 |
| Pretok [l/min] | 380 |