

Pre-filter without differential pressure gauge, 1 μ m, G 3/8

Kategorija: [Pre-filter without differential pressure gauge](#)Šifra: **199802RIE**

(slika je simbolična)

Kratek opis

Pre-filter without differential pressure gauge, 1 μ m, G3/8, Input pressure 4-12 bar, medium/ambient temp. 1.5 to 80°C, autom. drain valve
For filtering out solid impurities larger than 3 μ m and for moisture separation.
For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

Tehnične Specifikacije

Element filtra	Borosilicate microfibreglass fabric
Merjenje pretoka	At $P_1 = 7$ bar and pressure drop $\Delta_p = 0.1$ bar
Navoj	G 3/8
Ohišje	Aluminium
Posoda filtra	Aluminium
Vsebnost olja v ostanku [mg/m ³]	0.5
Ločevanje delcev [μ m]	1
Rang filtra [μ m]	1
Min. sobna temperatura [°C]	1.5
Min. temperatura medija [°C]	1.5
Min. vhodni tlak [bar]	4
Max. vhodni tlak [bar]	12
C [mm]	23.5
A [mm]	80.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
Učinkovitost [%]	99.99
D [mm]	327.0
Pretok [l/min]	1000