



(slika je simbolična)

Predfilter »FUTURA-mali« Kov. pos. 0.3 µm, Vel. 0, G 1/4

Kategorija: [Pre-filter with metal bowl](#)
Šifra: **142446RIE**

Kratek opis

Pre-filter »FUTURA-mini« with metal container, 0.3 µm, Size 0, G 1/4, PE 1.5 - 12 bar, Temp. -10 °C to 50 °C, Semi-automatic

Pre-filters in modern design for compliance with strict compressed air purity requirements.

Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Metal container
Priključni navoj	Plastic
Serijska	FUTURA-mini
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Rang filtra [µm]	0.3
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	12
C [mm]	27.0
A [mm]	43.0
Max. temperaturno območje [°C]	50
B [mm]	132.0
Pretok [l/min]	140