



(slika je simbolična)

## Predfilter»FUTURA«PC zbir.0.3 µmVel. 4G 1Avt.

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)Šifra: **100168RIE**

### Kratek opis

Pre-filter »FUTURA« with PC container and protective cage, 0.3 µm, Size 4, G 1, 1.5 - 16 bar, Temp. -10°C to 50°C, Fully-automatic

Pre-filters in modern design for compliance with strict compressed air purity requirements.

Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.02 bar
Merjenje pretoka	G 1
Navoj	Fully-automatic
Odtok kondenzata	PA66 GF60
Ohišje	Polycarbonate container with protective cage
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	0.3
Rang filtra [µm]	1.5
Min. vhodni tlak [bar]	4
Velikost	16
Max. vhodni tlak [bar]	50
Max. temperaturno območje [°C]	63.0
C [mm]	85.0
A [mm]	269.0
B [mm]	1500
Pretok [l/min]	