



(slika je simbolična)

## Predfilter»FUTURA«PC zbir.0.3 µmVel.4,G 3/4Avt.

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)Šifra: **100167RIE**

### Kratek opis

Pre-filter »FUTURA« with PC container and protective cage, 0.3 µm, Size 4, G 3/4, 1.5-16 bar, Temp. -10°C to 50°C, Fully-automatic  
Pre-filters in modern design for compliance with strict compressed air purity requirements.  
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10  |
| Element filtra                 | Impregnated paper<br>At P <sub>2</sub> = 6 bar and<br>pressure drop Δ <sub>p</sub> = 0.02<br>bar |
| Merjenje pretoka               | G 3/4<br>Fully-automatic<br>PA66 GF60<br>Polycarbonate container<br>with protective cage         |
| Navoj                          | Material: Die-cast zinc<br>FUTURA  |
| Odtok kondenzata               | Compressed air, neutral<br>gases   |
| Ohišje                         |  |
| Posoda                         |  |
| Priključni navoj               |  |
| Serijska                       |  |
| Srednje                        |  |
| Rang filtra [µm]               | 0.3  |
| Min. vhodni tlak [bar]         | 1.5  |
| Velikost                       | 4  |
| Max. vhodni tlak [bar]         | 16   |
| Max. temperaturno območje [°C] | 50   |
| C [mm]                         | 63.0   |
| A [mm]                         | 85.0   |
| B [mm]                         | 269.0  |
| Pretok [l/min]                 | 1500   |