



(slika je simbolična)

## [Prefilter »multifix« PC zbir.Zašč. kletkaVel. 4G 1](#)

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)Šifra: **133116RIE**

### Kratek opis

Pre-filter »multifix« with PC container and protective cage,  
0.3  $\mu\text{m}$ , Size 4, G 1, Input pressure max. 16 bar, Temp. max.  
60 °C  
For filtering out solid impurities larger than 0.3  $\mu\text{m}$ .

### Tehnične Specifikacije

Element filtra	Paper-POM
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.02$ bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	multifix
Tesnilo	NBR
Rang filtra [ $\mu\text{m}$ ]	0.3
Velikost	4
Max. vhodni tlak [bar]	16
DN	25
C [mm]	58.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	85.0
Učinkovitost [%]	99.999
D [mm]	190.0
B [mm]	248.0
Pretok [l/min]	2000