



(slika je simbolična)

Predfiltrirajte brez diferencialnega tlaka, 3 µm, G 3/8

Kategorija: [Pre-filter without differential pressure gauge](#)Šifra: **101553RIE**

Kratek opis

Pre-filter without differential pressure gauge, 3 µm, G 3/8,
Input pressure 4 - 12 bar, Medium / ambient temperature 5
°C to 60 °C

For filtering out solid impurities larger than 3 µm and for
moisture separation.

For connection upstream of a micro-filter or a combination
micro-filter/activated carbon filter.

Tehnične Specifikacije

Element filtra	Borosilicate microfibre fabric
Ločevanje delcev [µm]	from 3
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p =$ 0.5%
Navoj	G 3/8
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [µm]	3
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
C [mm]	57.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	83.0
Učinkovitost [%]	99.99
B2 [mm]	335.0
D [mm]	353.0
Pretok [l/min]	1000