

Datum: 24.08.2024



(slika je simbolična)

[Predfiltrirajte z diferenčnim manometrom, 3 µm, G 1 1/2](#)

Kategorija: [Pre-filter with differential pressure gauge](#)Šifra: **101550RIE**

Kratek opis

Pre-filter with differential pressure gauge, 3 µm, G 1 1/2,
Input pressure 4 - 12 bar, Medium / ambient temperature 5 °C to 60 °C

For filtering out solid impurities larger than 3 µm and for moisture separation.

For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

Tehnične Specifikacije

Element filtra	Polyethylene (with 45% cavity)
Ločevanje delcev [µm]	from 3
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.5\%$
Navoj	G 1 1/2
Ohišje	Aluminium
Posoda filtra	Aluminium
Max. označeni razpon diferenčnega manometra [bar]	2
Rang filtra [µm]	3
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
Učinkovitost [%]	99.99
A [mm]	118.0
B2 [mm]	620.0
B1 [mm]	717.5
D [mm]	858.0
Pretok [l/min]	8300