

Datum: 24.08.2024



(slika je simbolična)

## Prenosni krog. ventil za vodo, Z ročico, ročni, IT/IT, 1 1/2

Kategorija: [Potable water ball valves](#)  
Šifra: **103412RIE**

### Kratek opis

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20°C to 150°C, Rp 1 1/2, DN 40, PN max 30 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Aplikacije	Potable water, water
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Navoj	Rp 1 1/2
Ohišje	Chrome-plated brass
Ročica	Steel with plastic coating
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	NBR / FKM
E [mm]	21.4
PN [bar]	30
DN	40
a/f [mm]	54
B [mm]	91.8
L [mm]	109.0
Max. delovna temperatura [°C]	150
A [mm]	158.0