

Datum: 24.08.2024



(slika je simbolična)

Prenosni krogelni ventil za vodo, Z ročico, ročni, IT/IT, Rp 3/4

Kategorija: [Potable water ball valves](#)
Šifra: **103409RIE**

Kratek opis

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20°C to 150°C, Rp 3/4, DN 20, PN max. 40 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Aplikacije	Potable water, water
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Navoj	Rp 3/4
Ohišje	Chrome-plated brass
Ročica	Steel with plastic coating
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	NBR / FKM
E [mm]	16.3
DN	20
a/f [mm]	31
PN [bar]	40
B [mm]	56.3
L [mm]	68.0
A [mm]	113.5
Max. delovna temperatura [°C]	150