

Datum: 27.07.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Pretočni ventil, ET spodaj, aluminij, krogelni ventil

Kategorija: [Check valve, male thread at bottom](#)
Šifra: **108430RIE**

Kratek opis

Flow valve, ET bottom, required suction capacity $p_u = 0.3$ bar 8.1 l/min, $p_u = -0.6$ bar l/min 9.0, Aluminium, Ball seat valve

Check valves close the vacuum line if the suction pad is not covered, thus maintaining the vacuum. The valves are protected against dirt by a replaceable sieve. This valve series is suitable for all suction pads in our standard range.

Tehnične Specifikacije

Navoj 1	G 1/2 IT
Navoj 2	G 1/2 ET
Ohišje	Aluminium
Vrsta gradnje	Ball seat valve (ball in brass seat)
Zahtevana stopnja evakuacije za $p_u = -0.3$ bar [l/min]	8.1
Zahtevana stopnja evakuacije za $p_u = -0.6$ bar [l/min]	9
Dolžina [mm]	29.0
Teža [g]	47.4
Max. Izpušna pretočna hitrost [l/min]	790