

Datum: 24.08.2024



(slika je simbolična)

## Ravni pot.i fitting Metallica G 1/8 , Cev zunanja Ø 10

Kategorija: [Male connector, parallel male thread with O-ring](#)  
Šifra: **108859RIE**

### Kratek opis

Straight push-in fitting »metallica«, G 1/8 o., for hose exterior Ø 10 mm, Working pressure -0.98 to 16 bar, nickel-plated brass

Push-in fittings, manufactured entirely in nickel-plated brass.

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

### Tehnične Specifikacije

|                               |  |
|-------------------------------|--|
| Min. delovna temperatura [°C] | -20  |
| Min. delovni tlak [bar]       | -0.98  |
| Material                      | Nickel-plated brass                                    |
| Navoj                         | G 1/8  |
| Priporočena cev               | PA and PU  |
| Rokav                         | Nickel-plated brass                                    |
| Serija                        | metallica  |
| Vpenjalni obroč               | Male connector, parallel male thread with O-ring (FPM) |
| Zunanji šesterokotnik         | With   |
| Za cevi O.D. [mm]             | 10   |
| a/f [mm]                      | 16   |
| Max. delovni tlak [bar]       | 16   |
| L1 [mm]                       | 29.0   |
| Max. delovna temperatura [°C] | 150  |