

Datum: 03.11.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Ravni vtični konektor z vtičem nastavek 16 mm, zmanjšanje

Kategorija: [Reducers with push-in plug »Stainless steel«](#)  
Šifra: **135291RIE**

### Kratek opis

Straight push-in connector with plug nipple 16 mm, reducing, for hose exterior Ø 12 mm Working pressure -0.98 - 20 bar, 1.4404

For use in more aggressive environments and corrosive media.

Only recommended for use in combination with stainless steel quick connectors type 844 ff. Suitability testing for use with other series is the responsibility of the user.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel 1.4404
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Za cevi O.D. [mm]	12
Priključek [mm]	16
Max. delovni tlak [bar]	20
L1 [mm]	47.8
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150