

Datum: 03.07.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## Reducirni nastavek 246, N.N./Z.N.Rp 3/8,R 1/4

Kategorija: [Socket 246, reducing, female/male](#)  
Šifra: **113115RIE**

(slika je simbolična)

### Kratek opis

Reducing sleeve 246, IT/ET, Rp 3/8, R 1/4, Operating temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20   |
| Material                       | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj 1                        | Rp 3/8  |
| Navoj 2                        | R 1/4   |
| Površina                       | Hot dip galvanised                                  |
| Standardni navoj               | acc. ISO 7-1  |
| Max. temperaturno območje [°C] | 300   |