

Regulator stalnega tlaka, Velikost 2, G 3/8, 0.5 - 3 bar

Kategorija: [Constant-pressure regulators](#)
Šifra: **100877RIE**

(slika je simbolična)

Kratek opis

Constant pressure regulator incl. pressure gauge, Size 2, G 3/8, Input pressure max. 25 bar, Control range 0.5 - 3 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.
The pressure regulators maintain a constant working pressure regardless of variations in the inlet pressure.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Ohišje | Die-cast zinc |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 2 |
| Max. krmilno območje [bar] | 3 |
| DN | 15 |
| Max. vhodni tlak [bar] | 25 |
| C [mm] | 32.0 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 90.0 |
| Max. sobna temperatura [°C] | 90 |
| D [mm] | 138.0 |
| B [mm] | 170.0 |
| Pretok [l/min] | 3500 |