

## Serv. enota 2-delna »FUTURA« Kov. Vel.1, G 1/4, 0.1-1 Avt.

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)  
Šifra: **152418RIE**

(slika je simbolična)

### Kratek opis

Service unit 2-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 1, G 1/4, Control range 0.1-1 bar, Fully  
Two-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra Membrane	Cellpor (PE) NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.1
Max. krmilno območje [bar]	1
Velikost	1
Min. vhodni tlak [bar]	1.5
Zaslon manometra max. [bar]	1.6
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	96.0
A [mm]	104.0
B [mm]	243.0
Pretok [l/min]	1750