

Datum: 03.07.2024



(slika je simbolična)

## [Serv. enota 2-delna »Stinard«Kov. pos.Vel. 3G 1/2](#)

Kategorija: [Service unit, 2-piece with metal bowl](#)Šifra: **101061RIE**

### Kratek opis

Service unit 2-part »Standard«, Metal container, metal drip cap, Size 3, G 1/2, Input press. max. 25 bar, Control range 0.5-16 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Metal container
Serija	Standard
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [ $\mu$ m]	5
DN	15
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	25
Zaslon manometra max. [bar]	25
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer $\varnothing$ [mm]	63
C [mm]	130.0
A [mm]	175.0
B [mm]	302.0
Pretok [l/min]	2100