



(slika je simbolična)

Serv. enota 2-delna »Stinard«Kov. pos.Vel.1,G 3/8

Kategorija: [Service unit, 2-piece with metal bowl](#)
Šifra: **101059RIE**

Kratek opis

Service unit 2-part »Standard«, Metal container, metal drip cap, Size 1, G 3/8, Input press. max. 25 bar, Control range 0.5-16 bar
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Manuel |
| Ohišje | Die-cast zinc / aluminium, painted silver |
| Posoda | Metal container |
| Serijska | Standard |
| Tesnilo | NBR |
| Vidna kupola | Zinc-glass-NBR |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 1 |
| Rang filtra [μ m] | 5 |
| DN | 6 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 25 |
| Zaslon manometra max. [bar] | 25 |
| Manometer \varnothing [mm] | 50 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| C [mm] | 106.5 |
| A [mm] | 117.0 |
| B [mm] | 240.0 |
| Pretok [l/min] | 600 |