

Datum: 02.10.2024



(slika je simbolična)

Serv. enota 2-delna »Stinard« z PC zbir.Vel. 3G 1/2

Kategorija: [Service unit, 2-piece with polycarbonate bowl](#)
Šifra: **101049RIE**

Kratek opis

Service unit 2-part »Standard« with polycarbonate container, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.5 - 10 bar
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Semi-automatic Die-cast zinc / aluminium, painted silver
Ohišje	Polycarbonate container
Posoda	Standard
Serijska	NBR
Tesnilo	PA
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
DN	15
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer \varnothing [mm]	63
C [mm]	130.0
A [mm]	175.0
B [mm]	299.4
Pretok [l/min]	2100