



(slika je simbolična)

[Serv. enota 2-delna »variobloc«Kov. pos.Vel.1,G 1/4](#)

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)
Šifra: **125345RIE**

Kratek opis

Service unit 2-part »variobloc«, Metal container incl. viewing tube and metal drip cap, Size 1, G 1/4, Input pressure max. 20 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Serija	variobloc
Tesnilo	NBR
Vidna kupola	PA
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	0.5
Velikost	1
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	10
Max. vhodni tlak [bar]	20
Rang filtra [μ m]	40
C [mm]	68.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
A [mm]	96.0
B [mm]	203.0
Pretok [l/min]	1500