



(slika je simbolična)

Serv. enota 3-delna »FUTURA« Kov. Vel.2, G 1/2, 0.5-16 Avt.

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)
Šifra: **152710RIE**

Kratek opis

Service unit 3-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 2, G 1/2, Control range 0.5-16 bar, Fully
Three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra Membrane | Cellpor (PE) NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/2 |
| Odtok kondenzata | Fully-automatic |
| Ohišje | PA66 GF60 |
| Posoda | Metal container with viewing tube |
| Priključni navoj | Material: Die-cast zinc |
| Serijska | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Vidna kupola | PC |
| Min. krmilno območje [bar] | 0.5 |
| Min. vhodni tlak [bar] | 1.5 |
| Velikost | 2 |
| Rang filtra [μ m] | 5 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 16 |
| Zaslona manometra max. [bar] | 25 |
| Max. temperaturno območje [°C] | 50 |
| C [mm] | 110.0 |
| A [mm] | 189.0 |
| B [mm] | 277.0 |
| Pretok [l/min] | 3500 |