

Serv. enota 3-delna»FUTURA«Kov. Vel.4, G1, 0.5-16 Pol avto.

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)
Šifra: **152686RIE**

(slika je simbolična)

Kratek opis

Service unit 3-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 4, G 1, Control range 0.5 - 16 bar, Semi

Three-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra Membrane | Cellpor (PE) NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | PA66 GF60 |
| Poraba zraka | Yes |
| Posoda | Metal container with viewing tube |
| Priključni navoj | Material: Die-cast zinc |
| Serija | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Vidna kupola | PC |
| Min. krmilno območje [bar] | 0.5 |
| Max. notranja poraba zraka | 1.5 l/min (depending on secondary pressure) |
| Min. vhodni tlak [bar] | 1.5 |
| Velikost | 4 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 16 |
| Zaslon manometra max. [bar] | 25 |
| Max. temperaturno območje [°C] | 50 |
| C [mm] | 137.0 |
| A [mm] | 255.0 |
| B [mm] | 326.0 |
| Pretok [l/min] | 12000 |