

Datum: 24.08.2024



(slika je simbolična)

[Serv. enota 3-delna »G«PC zbir.5 µmVel. 300G 3/8](#)

Kategorija: [Service unit, 3-piece with PC bowl, bowl guard](#)
Šifra: **116419RIE**

Kratek opis

Service unit 3-part »G«, PC container, Protective cage, 5 µm, Size 300, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar
Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Polycarbonate container with protective cage |
| Serija | G |
| Tesnilo | NBR |
| Vidna kupola | Brass/POM |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| C [mm] | 44.0 |
| Max. sobna temperatura [°C] | 70 |
| Max. temperatura medija [°C] | 70 |
| D [mm] | 143.0 |
| A [mm] | 179.0 |
| B [mm] | 187.0 |
| Velikost | 300 |
| Pretok [l/min] | 1400 |