



(slika je simbolična)

Serv. enota 3-delna »multifix«Kov. pos.Vel. 5G 1

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)
Šifra: **100595RIE**

Kratek opis

Service unit 3-part »multifix«, Metal container, Viewing tube, Size 5, G 1, Input pressure max. 20 bar, Control range 0.5 - 10 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Aluminium |
| Posoda | Metal container with viewing tube |
| Serija | multifix |
| Tesnilo | NBR |
| Vidna kupola | Zinc-glass-NBR |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 5 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 16 |
| Max. vhodni tlak [bar] | 20 |
| DN | 25 |
| Rang filtra [μ m] | 40 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| C [mm] | 128.0 |
| D [mm] | 255.7 |
| A [mm] | 300.0 |
| B [mm] | 383.7 |
| Pretok [l/min] | 13500 |