



(slika je simbolična)

## Service unit 2-delna »Stinard« z PC zbiralnik, Velikost 4, G 1

Kategorija: [Service unit, 2-piece with polycarbonate bowl](#)  
Šifra: **174099RIE**

### Kratek opis

Service unit 2-part »Standard« with polycarbonate container, Size 4, G 1, PE max. 16 bar, Control range 0.5 - 10 bar, pilot contr.  
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p_p = 1$ bar
Navoj	G 1
Odtok kondenzata	Semi-automatic Die-cast zinc / aluminium, painted silver
Ohišje	Polycarbonate container
Posoda	Standard
Serija	NBR
Tesnilo	PA
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	4
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	16
DN	25
Rang filtra [ $\mu$ m]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer $\varnothing$ [mm]	63
C [mm]	129.0
A [mm]	222.0
B [mm]	392.0
Pretok [l/min]	4000