



(slika je simbolična)

## Servisna enota VARNOSTNA »FUTURA«, Velikost 1, G 3/8

Kategorija: [SAFETY service unit set](#)  
Šifra: **100268RIE**

### Kratek opis

Service station SAFETY »FUTURA«, Ball valve - start-up valve - 2-part service unit, Size 1, G 3/8, Input pressure 2.5 - 16 bar

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Element filtra                 | Cellpor (PE)  |
| Membrane                       | NBR   |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Merjenje pretoka               | G 3/8   |
| Navoj                          | Fully-automatic   |
| Odtok kondenzata               | Silencer (ball valve)   |
| Odzračevalni vtič              | PA66 GF60   |
| Ohišje                         | Material: Die-cast zinc   |
| Priključni navoj               | FUTURA  |
| Serijska                       | Compressed air, neutral gases   |
| Srednje                        | NBR   |
| Tesnilo                        | 1   |
| Velikost                       | 2.5   |
| Min. krmilno območje [bar]     | 2.5   |
| Min. vhodni tlak [bar]         | 5   |
| Rang filtra [µm]               | 8   |
| Max. krmilno območje [bar]     | 10  |
| Zaslon manometra max. [bar]    | 16  |
| Max. vhodni tlak [bar]         | 50  |
| Max. temperaturno območje [°C] | 96.0  |
| C [mm]                         | 208.0   |
| A [mm]                         | 243.0   |
| B [mm]                         | 1750  |
| Pretok [l/min]                 |   |