



(slika je simbolična)

Servisna enota VARNOSTNA »FUTURA«, Velikost 2, G 3/8

Kategorija: [SAFETY service unit set](#)
Šifra: **100269RIE**

Kratek opis

Service station SAFETY »FUTURA«, Ball valve - start-up valve - 2-part service unit, Size 2, G 3/8, Input pressure 2.5 - 16 bar

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Cellpor (PE) |
| Membrane | NBR |
| | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Merjenje pretoka | G 3/8 |
| Navoj | Fully-automatic |
| Odtok kondenzata | Silencer (ball valve) |
| Odzračevalni vtič | PA66 GF60 |
| Ohišje | Material: Die-cast zinc |
| Priključni navoj | FUTURA |
| Serijska | Compressed air, neutral gases |
| Srednje | NBR |
| Tesnilo | 2 |
| Velikost | 2.5 |
| Min. krmilno območje [bar] | 2.5 |
| Min. vhodni tlak [bar] | 5 |
| Rang filtra [µm] | 8 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 16 |
| Max. vhodni tlak [bar] | 50 |
| Max. temperaturno območje [°C] | 110.0 |
| C [mm] | 252.0 |
| A [mm] | 273.0 |
| B [mm] | 3500 |
| Pretok [l/min] | |