

Datum: 03.07.2024



(slika je simbolična)

## stand. cilinderdelujoč v dveh smerehbat Ø 40hod 500G 1/4

Kategorija: [Metalwork](#)Šifra: **106201RIE**

### Kratek opis

Standard cylinder, ISO 15552, double-acting, Piston Ø 40, Stroke 500, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.

The version with a 125 mm bore is provided with fixing accessories on three sides as standard.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10  |
| Bat                            | POM  |
| Batnica                        | C45 steel, hard chrome-plated  |
| Cushioning                     | cushioned  |
| ET batnice                     | M12x1.25   |
| Ffunkcija                      | double-acting  |
| Gewinde Kolbenstange           | male piston rod  |
| Magnet                         | with magnet  |
| Navoj na batnici               | M12x1.25   |
| Oblika                         | Heads / jacket with self-tapping screws<br>Anodised aluminium jacket with integrated T-slots |
| Ovoj                           | G 1/4  |
| Povezava                       | acc. to ISO 15552  |
| Standard                       | NBR  |
| Tesnilo                        | 0.4  |
| Min. nastavljeni tlak [bar]    | 10   |
| Max. delovni tlak [bar]        | 16   |
| Batnica Ø [mm]                 | 40   |
| Bat Ø [mm]                     | 16   |
| Max. temperaturno območje [°C] | 80   |
| Stroke [mm]                    | 500  |