

Datum: 24.08.2024



(slika je simbolična)

## Standardni manometer, prikllop spodaj, G 1/2, 0 - 25 bar, Ø 160

Kategorija: [Wika](#)  
Šifra: **101995RIE**

### Kratek opis

Standard pressure gauge, Single scale bar, Connection radial bottom, G 1/2, Goods class 1.6, Measurement range 0 - 25 bar, Ø 160  
Bourdon-tube pressure gauge in standard design.  
Suitable for gaseous or liquid media which do not corrode copper alloy,  
do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Sheet steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Flat instrument glass
Premikanje	Copper alloy
Referenčni kazalnik	red
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.5
Razred točnosti	1.6
Merilno območje max. bar	25
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Vrsta	111.10
Premer [mm]	160