

Datum: 24.08.2024



(slika je simbolična)

## Stenski priključki hN.N.rih spoj s priključnicami I.D. 7.2

Kategorija: [Distributor for wall mountable with coupling DN7.2](#)  
Šifra: **107272RIE**

### Kratek opis

Distributor for wall mounting with quick-connect couplings I.D. 7.2, Bright brass, G 1/2 IT, Operating pressure 0 - 35 bar  
1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.  
Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 IT
Spojke	DN 7.2, brass with a bare metal surface, G 1/2 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Sestava distributerja	5 x G 1/2 outlets
Max. obratovalni tlak [bar]	35
Višina [mm]	57.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Premer [mm]	113.0