

**Datum:** 02.10.2024



(slika je simbolična)

## Temperaturna sklopka DN 9, navoj 13 mm, Medenina, cevFi cevi 45°

Kategorija: [Temp. control coupl. DN 9, without shut-off valve](#)  
Šifra: **107957RIE**

### Kratek opis

Tempered coupling DN 9, Taps 13 mm, Brass, Hose sleeve 45°, Operating pressure max. 15 bar, Medium/ambient temp. -20 °C to 160 °C  
Compatible with HASCO Z 8 system.  
For temperature control applications involving hot or cold water or heat transfer oil.  
Optionally with free passage, one or both sides sealing.  
Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Priključek za cev [mm]	13
Max. obratovalni tlak [bar]	15
Tip stebelnih cevi	45°
Dolžina [mm]	50.5
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160