

Datum: 24.08.2024



(slika je simbolična)

Tlačni regulator DRV 250, Low pressure design, G 3/8, 0.2-2 bar

Kategorija: [DRV 250 pressure regulator, low-pressure type](#)Šifra: **101435RIE**

Kratek opis

Pressure regulator DRV 250, Low pressure design, non-reversible, incl. pressure gauge, G 3/8, Control range 0.2 - 2 bar

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment and good response characteristic because there are only a few moving parts and hence minimal friction.

Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Tehnične Specifikacije

| | |
|---|---------------|
| Navoj | G 3/8 |
| Ohišje | Red brass |
| | 2.1096.01 |
| Tesnilo | NBR |
| Vzmet pokrova motorja | Pressed brass |
| Min. krmilno območje [bar] | 0.2 |
| Pretok KVS vrednost [m ³ /h] | 0.6 |
| Max. krmilno območje [bar] | 2 |
| DN | 10 |
| Razmerje zmanjšanja max. | 20:1 |
| Max. vhodni tlak [bar] | 25 |
| D [mm] | 45.5 |
| A [mm] | 70.0 |
| Max. temperaturno območje [°C] | 75 |
| C [mm] | 140.0 |
| B [mm] | 185.5 |