

Datum: 24.08.2024



Tlačni regulator »Stinard«, Velikost 4, G 1 1/2, 0.5 - 16 bar

Kategorija: [Pressure regulators](#)Šifra: **100830RIE**

(slika je simbolična)

Kratek opis

Pressure regulator »Standard«, Size 4, G 1 1/2, Input pressure max. 25 bar, Medium temp. max. 60 °C, Control range 0.5 - 16 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1 1/2 |
| Ohišje | Die-cast zinc, painted silver |
| Serija | Standard |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 4 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 25 |
| Zaslona manometra max. [bar] | 25 |
| DN | 35 |
| C [mm] | 52.0 |
| Max. temperatura medija [°C] | 60 |
| Max. sobna temperatura [°C] | 80 |
| A [mm] | 125.0 |
| D [mm] | 200.5 |
| B [mm] | 252.5 |
| Pretok [l/min] | 16500 |