

Datum: 02.10.2024



(slika je simbolična)

## Tlačni regulator »variobloc«, Velikost 2, G 1/2, 0.5 - 16 bar

Kategorija: [Pressure regulators](#)  
Šifra: **100642RIE**

### Kratek opis

Pressure regulator »variobloc«, incl. pressure gauge, Size 2, G 1/2, Input pressure max. 25 bar, Control range 0.5 - 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Membrane                     | NBR   |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/2   |
| Ohišje                       | Die-cast zinc   |
| Serija                       | variobloc   |
| Tesnilo                      | NBR   |
| Vzmet pokrova motorja        | POM   |
| Min. krmilno območje [bar]   | 0.5   |
| Velikost                     | 2   |
| Max. krmilno območje [bar]   | 16  |
| Zaslon manometra max. [bar]  | 16  |
| Max. vhodni tlak [bar]       | 25  |
| C [mm]                       | 33.0  |
| A [mm]                       | 70.0  |
| Max. sobna temperatura [°C]  | 80  |
| Max. temperatura medija [°C] | 80  |
| B [mm]                       | 134.0   |
| Pretok [l/min]               | 7000  |