

Datum: 03.07.2024



## Tlačni regulator »variobloc«, Velikost 2, G 3/4, 0.5 - 10 bar

Kategorija: [Pressure regulators, continuous pressure supply](#)Šifra: **149192RIE**

(slika je simbolična)

### Kratek opis

Pressure regulator, continuous pressure supply »variobloc«, Size 2, G 3/4, Input pressure max. 25 bar, Control range 0.5 - 10 bar

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the knob down. By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Ohišje	Die-cast zinc
Povezava zadaj	G 1/2
Serija	variobloc
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Velikost	2
Max. krmilno območje [bar]	10
Zaslona manometra max. [bar]	10
Max. vhodni tlak [bar]	25
C [mm]	33.0
A [mm]	70.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
B [mm]	134.0
Pretok [l/min]	6800