



(slika je simbolična)

## Umerjanje in servisna oprema, -0.95 / 40 bar, G 1/4

Kategorija: [Wika](#)  
Šifra: **102758RIE**

### Kratek opis

Calibration test and service equipment, Measurement range -0.95 / +40 bar, G 1/4, incl. factory calibration certificate  
Service case for quick and precise pressure gauge calibration.

Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance.

Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point.

Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed.

Includes a plastic emergency case with foam padding.

### Tehnične Specifikacije

Min. temperatura medija [°C]	-20
Min. sobna temperatura [°C]	-10
Merilno območje min. bar	-0.95
Deli v kontaktu z medijem	CrNi steel with NBR seal
Ohišje	Die-cast zinc
Povezava	G 1/4
Natančnost	0.25% FS
Merilno območje max. bar	40
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	80