

Datum: 27.07.2024



(slika je simbolična)

Varn krog. ventil z vzmetnim povratkom, nikljana med., 2

Kategorija: [Safety ball valves with spring return](#)
Šifra: **103234RIE**

Kratek opis

Safety ball valve with spring reset, nickel-plated brass,
Operating temperature -40 °C to 170 °C, Rp 2, DN 50, PN
max. 40 bar

"

2/2-way safety ball valves, two parts, made of nickel-plated
brass with spring return.

The ball valve is closed in the normal position and opens
against spring force. High safety standard because the valve
is automatically closed if the handle is not operated

Tehnične Specifikacije

| | |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -40 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | Rp 2 |
| Ohišje | Nickel-plated brass |
| Ročica | Steel - PVC coated |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Stebelno tesnilo | FKM |
| Vzmet | Stainless steel 1.4301 |
| PN [bar] | 40 |
| DN | 50 |
| B [mm] | 88.0 |
| L [mm] | 140.0 |
| A [mm] | 158.0 |
| Max. delovna temperatura [°C] | 170 |