

Datum: 26.12.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varn. ventil, med., G 1 1/2, vkl. prit. 16 bar

Kategorija: [Varnostni ventil G 1 1/2](#)
Šifra: **105042RIE**

Kratek opis

Safety valve, High performance design, Brass, Operating temp. -40 °C to 200 °C, G 1 1/2, AF 55, Trigger pressure 16 bar

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

These valves are TÜV approved and have a TÜV type test number.

Tehnične Specifikacije

| | |
|-------------------------------|---------|
| Min. delovna temperatura [°C] | -40 |
| Navoj | G 1 1/2 |
| Ohišje | Brass |
| Tesnilo | FPM |
| Tlačna vzmet | C steel |
| Min. obratovalni tlak [bar] | 0.5 |
| Min. nastavljeni tlak [bar] | 16 |
| A [mm] | 22.0 |
| Max. obratovalni tlak [bar] | 26 |
| narediti [mm] | 32.0 |
| a/f [mm] | 55 |
| H [mm] | 178.0 |
| Max. delovna temperatura [°C] | 200 |