

Datum: 03.11.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varn.ventil s pol. hod. DN 10, G 3/4, vkl. prit. 4.3 bar

Kategorija: [Varnostni ventil G 3/4](#)
Šifra: **202449RIE**

Kratek opis

Full stroke safety valve DN 10, Brass, Operating temp. -25 °C to 180 °C, G 3/4, AF 32, Trigger pressure 4.3 bar, Type tested
For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.
These valves are TÜV approved and have a TÜV type test number.

Tehnične Specifikacije

| | |
|-------------------------------|-----------------|
| Min. delovna temperatura [°C] | -25 |
| Navoj | G 3/4 |
| Ohišje | Brass |
| Tesnilo | FKM |
| Tlačna vzmet | Stainless steel |
| Min. obratovalni tlak [bar] | 0.2 |
| Min. nastavljeni tlak [bar] | 4.3 |
| D [mm] | 16.0 |
| A [mm] | 32.0 |
| a/f [mm] | 32 |
| Max. obratovalni tlak [bar] | 50 |
| C [mm] | 75.0 |
| Max. delovna temperatura [°C] | 180 |