

Datum: 02.10.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varn.ventil s pol. hod. DN 8, G 3/8, vkl. prit. 2.8 bar

Kategorija: [Varnostni ventil G 3/8](#)
Šifra: **104132RIE**

Kratek opis

Full stroke safety valve DN 8, Brass, Operating temperature -25 °C to 180 °C, G 3/8, AF 20, Trigger pressure 2.8 bar, Type tested
For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.
These valves are TÜV approved and have a TÜV type test number.

Tehnične Specifikacije

| | |
|-------------------------------|-----------------|
| Min. delovna temperatura [°C] | -25 |
| Navoj | G 3/8 |
| Ohišje | Brass |
| Tesnilo | FKM |
| Tlačna vzmet | Stainless steel |
| Min. obratovalni tlak [bar] | 0.2 |
| Min. nastavljeni tlak [bar] | 2.8 |
| D [mm] | 12.0 |
| A [mm] | 20.0 |
| a/f [mm] | 20 |
| Max. obratovalni tlak [bar] | 50 |
| C [mm] | 63.0 |
| Max. delovna temperatura [°C] | 180 |