

Datum: 03.07.2024



(slika je simbolična)

## Varnosta spojka I.D. 7.8Bi-Tec pocinkana Med.I.D. 13

Kategorija: [Safety coupling DN 7.8, with hose stem](#)  
Šifra: **107614RIE**

### Kratek opis

Safety coupling I.D. 7.8, Bi-Tec type, nickel-plated brass,  
Sleeve I.D. 13, Operating pressure max. 20 bar, Temp.  
-20°C to 100°C

Safety air relief couplings for gaseous media.

Combination of a sliding valve and a quick disconnect  
coupling!

Connection is pressureless. Only a low spring force has to be  
overcome. Pressure only builds up when the blue sleeve is  
pushed forward. It is impossible to disconnect the hose  
either intentionally or inadvertently in this position. When  
the sliding sleeve is moved back into its home position, the  
air is relieved from the hose and the coupling can be  
disconnected.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel at 6 bar and $\Delta_p = 0.5$ bar
Merjenje pretoka	Nickel-plated brass I.D. 13
Ohišje	Anodised aluminium
Povezava	Hardened, nickel-plated steel
Rokav	Nickel-plated brass
Sprostitutveni rokav	NBR
Telo ventila	Stainless steel
Tesnilo	7.8
Vzmet	20
DN	86.0
Max. obratovalni tlak [bar]	Max. sobna temperatura [°C]
Dolžina [mm]	100
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	1400 l/min (air)
Pretok	