

Datum: 24.08.2024



(slika je simbolična)

Varnostni krogelni ventil, z zaklepom, z izpustom, Rp 1 1/4

Kategorija: [Safety ball valves, lockable, with relief port](#)
Šifra: **103154RIE**

Kratek opis

Safety ball valve lockable, Venting hole G 1/4, nickel-plated brass, Operating temp. max. 100 °C, Rp 1 1/4, DN 32, PN max. 14 bar

Safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications.

The valve shuts off the supply line and bleeds the application area.

Lockable hand lever in closed position ensures a high protection against manipulation.

Tehnične Specifikacije

| | |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -10 |
| Bore diameter padlock | ca. 7.3 mm |
| Izpušni vtič | G 1/4 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | Rp 1 1/4 |
| Ohišje | Nickel-plated brass |
| Ročica | Steel - PVC coated |
| Standardni navoj | Rp thread acc. to EN 10226 |
| Stebelno tesnilo | FKM |
| Max. obratovalni tlak [bar] | 14 |
| DN | 32 |
| B [mm] | 80.0 |
| L [mm] | 93.0 |
| Max. delovna temperatura [°C] | 100 |
| A [mm] | 157.0 |