

Datum: 02.10.2024



(slika je simbolična)

Varnostni krogelni ventil, z zaklepom, z izpustom, Rp 3/4

Kategorija: [Safety ball valves, lockable, with relief port](#)
Šifra: **103152RIE**

Kratek opis

Safety ball valve, lockable, Venting hole M5, nickel-plated brass, Operating temp. -10 °C to 100 °C, Rp 3/4, DN 20, PN max. 14 bar
Safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications.
The valve shuts off the supply line and bleeds the application area.
Lockable hand lever in closed position ensures a high protection against manipulation.

Tehnične Specifikacije

| | |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -10 |
| Bore diameter padlock | ca. 7.3 mm |
| Izpušni vtič | M5 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | Rp 3/4 |
| Ohišje | Nickel-plated brass |
| Ročica | Steel - PVC coated |
| Standardni navoj | Rp thread acc. to EN 10226 |
| Stebelno tesnilo | FKM |
| Max. obratovalni tlak [bar] | 14 |
| DN | 20 |
| B [mm] | 60.0 |
| L [mm] | 64.0 |
| Max. delovna temperatura [°C] | 100 |
| A [mm] | 117.0 |