

Datum: 24.08.2024



Visoko zmogl. varnos.ventil, G 2, vkl. prit. 6.4 bar

Kategorija: [High-pressure Varnostni ventil G 2](#)
Šifra: **105403RIE**

(slika je simbolična)

Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 2, AF 80, Trigger pressure 6.4 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

Tehnične Specifikacije

| | |
|-------------------------------|------------------------------------|
| Navoj | G 2 |
| Ohišje | Brass |
| Vzmet pokrova motorja | Malleable iron, powder-coated blue |
| Min. obratovalni tlak [bar] | 0.5 |
| Min. nastavljeni tlak [bar] | 6.4 |
| A [mm] | 22.0 |
| Max. obratovalni tlak [bar] | 30 |
| narediti [mm] | 40.0 |
| a/f [mm] | 80 |
| Max. delovna temperatura [°C] | 260 |
| H [mm] | 367.0 |