



Visokotlačni reg. 60 barG 3/8Regulacijsko območje 0.5 - 12 bar

Kategorija: [High pressure regulators up to 60 bar](#)Šifra: **101147RIE**

(slika je simbolična)

Kratek opis

High pressure regulator 60 bar, G 3/8, Control range 0.5 - 12 bar, Input pressure max. 60 bar, Operating temp. -10 °C to 90 °C

Reversible piston-type pressure regulator, virtually independent of inlet pressure, with self-relieving design, manufactured entirely in brass.

Specially designed for high pressures up to 60 bar. Pressure catch with counter nut.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Aplikacije	Compressed air and other neutral, non-flammable gases At $P_1 = 20$ bar, $P_2 = 10$ bar and pressure drop $\Delta_p = 4$ bar
Merjenje pretoka	
Navoj	G 3/8
Ohišje	Brass
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Max. krmilno območje [bar]	12
C [mm]	31.0
Max. vhodni tlak [bar]	60
A [mm]	72.0
Max. delovna temperatura [°C]	90
D [mm]	133.0
B [mm]	164.0
Pretok [l/min]	2500